# EUROLITE Set PAR-16 Spot sil + GU-10 230V COB 5W LED 1800-3000K dim2warm

Art. Nr.: 20000687

PAR-16 housing with GU-10 socket including LED lamp with modern dim-to-warm-feature

GTIN: 4026397361582







## Features:

- Mini-spot for GU-10 lamp
- The device is cooled by passive convection cooling
- Control via plug and play
- With mounting bracket
- Available in various colors
- For PAR 16
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation

**mounting bracket**

- The article is delivered pre-assembled
- <p>OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm

**LED lamp with modern dim-to-warm feature**

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Dimmable
- Easy installation
- With a beam angle of 24°
- Variable color temperature 1800 K - 3000 K
- Very high color rendering index (CRI)

## Logistic

EAN / GTIN: 4026397361582

Weight: 0,50 kg

Length: 0.17 m

Width: 0.10 m

Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

## Technical specifications:

| | |
|---|---|
| Weight: | 0.32 kg |
| Energy efficiency class (A - G): | F |

**EUROLITE PAR-16 Spot GU-10 silver**

| | |
|---|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 75 W |
| Protection class: | Protection class I |
| Suitable lamp: | Max. 75 W PAR-16 GU10 |
| Power connection: | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 0.75 mm² H05SS-F |
| Cable length: | Approx. 0.4 m |
| Base: | GU10 |
| Lamp type: | Selectable |
| Color generation: | Via color filter frame |
| Cooling: | Passive convection cooling |
| Control: | Plug and play |
| Construction: | PAR-16 |
| Housing color: | Silver |
| Attachment system: | Mounting bracket |
| Material: | Aluminum |
| Slot for spot length: | 8 cm x 8 cm |
| Dimensions: | Length: 17 cm<br>Width: 11 cm<br>Height: 13 cm |
| Weight: | 0.28 kg |
| Noise classification: | Class 0 (no noise at all) |
| Diameter mounting holes: | 2 x Ø9mm |
| Material: | Aluminum |
| Shape: | Octagonal |
| Material: | Aluminum |
| Dimensions: | Length: 7.7 cm<br>Width: 7.7 cm<br>Diameter: Ø 5.3 cm |
| Weight: | 0.01 kg |

**OMNILUX GU-10 230V COB 5W LED 1800-3000K dim2warm**

| | |
|---|---|
| Operating voltage: | 230 V |
| Nominal wattage: | 5 W |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Base: | GU10 |
| Lamp type: | LED lamp; reflector lamp |
| Lamp specification: | Dimmable |
| PstLM: | 0.0 |
| Setup: | Easy installation |
| Beam angle: | 24° |
| Beam angle (1/2 peak): | 24° |
| Beam angle (1/10 peak): | 60° |
| Color of light: | White |
| Color temperature: | 1800K - 3000K adjustable |
| Color rendering index (CRI): | 90 Ra |
| Luminous flux maintenance: | 13 |
| MacAdam Color consistency: | 3 |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Lamp life: | 15000 h |
| Luminous flux: | 400 lm |
| Luminous flux maintenance: | 0.97 |
| Wavelength: | 640 nm |
| Material: | Aluminum casting |
| Dimensions: | Width: 5 cm<br>Depth: 5 cm<br>Height: 5 cm |
| Weight: | 0.04 kg |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 960770 |

## Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.