ROADINGER Flightcase 8x AKKU IP Pixel Tube 360° PRO CRMX with charging function and

Trunk case with castors

GTIN: 4026397742282











Features:

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 35mm with rounded edges
- 4 hinged, chromium plated case handles
- Edge mounting handle
- 3 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes Ø 100 mm
- 4 x built-in stacking trays in the cover

Logistic

EAN / GTIN: 4026397742282
Weight: 35,00 kg
Length: 1.19 m
Width: 0.63 m
Heigth: 0.45 m
Bulky product

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power connection:	Mains input via IP T-Con (M) power supply cord with safety plug (provided)
Cable construction:	3 x 1.5 mm² H07RN-F
Cable length:	1.2 m
Fuse:	5 x 20 mm, 5 A fuse replaceable
Aluminum profile frames:	35 mm
Case handle:	4 pc/pcs
Edge mounting handle:	1 pc/pcs
Stop hinge:	3 pc/pcs

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes Ø 100 mm 4 x built-in stacking trays in the cover
Color:	Black, laminated
Device compartment:	7 cm x 109 cm x 10 cm
Accessory compartment:	113 cm x 9 cm x 21 cm
Material thickness:	9 mm
Dimensions:	Width: 119 cm Depth: 63 cm Height: 43.5 cm
Weight:	34.80 kg

Scope of delivery:

1 x case
1 x power cord
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.