LAVOCE CSF082.00K 8" Coaxial Speaker, Ferrite, Steel Basket Driver

Art. No.: 12603020

200 W AES LF/35 W AES HF, 8 ohms LF/8 ohms HF, 96 dB LF/103.5 dB HF, 75-5500 Hz LF/1500-20000 Hz HF

GTIN: 4026397706086







Features:

- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 4026397706086

Technical specifications:

Power:	Program: 400W LF Rated: 200W AES LF Program: 70W HF Rated: 35W AES HF
Frequency range:	75 - 5500 Hz LF 1500 - 20000 Hz HF
Sensitivity:	96 dB LF; 103.5 dB HF
Impedance:	8 ohms LF; 8 ohms HF
Speaker:	Woofer 8" with shared ferrit magnet with dual demodulating rings Basket material: aluminum Voice coil lows 2" Diaphragmmaterial: Polyamide Compression tweeter highs 1" Voice coil compression tweeter highs 1.4"
Weight:	2.97 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Scope of delivery:

1 x speaker

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.