EUROLITE Set PAR-30 Spot bk + PAR-30 230V COB 12W E-27 LED 1800-3000K dim2warm

Art. No.: 20120330

PAR-30 housing with E-27 socket including PAR-30 LED lamp with modern dim-to-warm-feature

GTIN: 4026397362367







Features:

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- <p>OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

PAR-30 LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Dimmable
- Easy installation
- Variable color temperature 1800 K - 3000 K
- Very high color rendering index (CRI)

Logistic

EAN / GTIN: 4026397362367

Weight: 1,00 kg

Length: 0.30 m

Width: 0.22 m

Heigth: 0.21 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Weight:	0.67 kg
Energy efficiency class (A - G):	F

EUROLITE PAR-30 Spot black

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 100 W
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/100 W E27
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm² H05SS-F
Cable length:	Approx. 0.4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-30
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	12.8 cm x 12.8 cm
Dimensions:	Length: 23.5 cm Width: 14.5 cm Height: 21 cm
Weight:	0.53 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Shape:	Octagonal
Material:	Aluminum, 0.5 mm
Dimensions:	Length: 12.6 cm Width: 12.6 cm Diameter: Ø 9.4 cm
Weight:	0.022 kg

OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

Operating voltage:	230 V
Nominal wattage:	12 W
Base:	E27

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Lamp type:	LED lamp; reflector lamp
Lamp specification:	Dimmable
Beam angle:	24°
Setup:	Easy installation
Color of light:	White
Color temperature:	1800K - 3000K adjustable
Color rendering index (CRI):	96 Ra
Construction:	PAR-30
Lamp life:	15000 h
Luminous flux:	960 lm
Wavelength:	640 nm
Weight:	0.14 kg
Photobiological safety:	Risk Group 1
Energy efficiency class (A - G):	F
EPREL-Nr:	963473

Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.