ALUTRUSS DECOLOCK DQ2-SPAT42H 4-way crosspiece bk

Universal 2-point truss system in lightweight construction

Art. No.: 60300152

GTIN: 4026397679083





Features:

- Innovative black powder coating for trendy designs
- Achieve dramatic effects in combination with appropriate lighting, lush greenplants, brass elements and white as a strong contrast
- Fast, efficient and reliable assembly via QUICK-LOCK conical connectors
- An extensive selection of lengths, circular and corner elements offers maximum flexibility
- Special designs according to customer specifications on request
- Direction horizontal
- Trusspipe: 35 mm
- Any RAL color available on request
- Various versions available
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; installation; stage

Logistic

EAN / GTIN: 4026397679083
Weight: 2,80 kg
Length: 0.64 m
Width: 0.42 m
Heigth: 0.42 m

Technical specifications:

Corner angle:	90°
Trusspipe:	35 mm x 2 mm
Alloy:	EN-AW 6060 T66 (AlMgSi0.5)
Color:	Black, powder-coated; any RAL color available on request
Strut diameter x thickness:	10 x 2mm
Dimensions:	Length: 58 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Width: 40 cm Height: 40 cm
Weight:	2.50 kg

Scope of delivery:

2 x connection set

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.