# EUROLITE Set 4x LED CLS-18 QCL RGB/WW 18x7W + Flightcase with wheels

**Item No.: 20001036**

GTIN: 4026397733082







## Features:

**EUROLITE LED CLS-18 QCL RGB/WW 18x7W**

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

- Additional frost filter provides a wide, soft and homogeneous light
- 18 LEDs 7 W  4in1 RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
- Strobe effect
- Can be operated in 3; 4; 6; 8; 11 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 11°
- Direct color temperature selection for 3100 preset values
- With mounting bracket
- OLED display
- Rubber feet
- For application areas such as: Stage; clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; party room
- Very quiet working noise

## Logistic

EAN / GTIN: 4026397733082

Weight: 40,50 kg

Length: 0.00 m

Width: 0.00 m

Heigth: 0.00 m

Bulky product

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Application possibility: Standing; suspended; on stand
- 3  buttons on the remote control for saving your own settings
  **knurled screw**
- M4 thread

**ROADINGER Flightcase 4x LED CLS-18 QCL RGB/WW with wheels**

Trunk case with castors

- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes

## Technical specifications:

| | |
|---|---|
| Weight: | 38.54 kg |

**EUROLITE LED CLS-18 QCL RGB/WW 18x7W**

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 104 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x PowerCON (grey) |
| Lamp type: | LED lamp |
| LED type: | 18 x 7 W  4in1 RGB/WW (homogenous color mix) |
| Flash rate: | 0.8 - 22 Hz |
| DMX channels: | 3; 4; 6; 8; 11 |
| DMX input: | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control |
| Fixtures available for: | Light´J; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 11° |
| Beam angle (1/2 peak): | 11°<br>Frost filter 15° |
| Beam angle (1/10 peak): | 26°<br>Frost filter 37° |
| Housing color: | Black matte |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Attachment system: | Mounting bracket |
| Display type: | OLED display |
| Transport aid: | Rubber feet |
| Dimensions: | Length: 39.6 cm<br>Width: 14.3 cm<br>Height: 21.3 cm |
| Weight: | 4.86 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Diameter mounting holes: | 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm |
| Material: | Metal, 2 mm |
| Cable construction: | 3 x 1.0 mm² H05VV-F |
| Cable length: | Approx. 1.2 m |
| Diameter mounting holes: | 4 x Ø4.5mm |
| Material: | Plastic, 2 mm |
| Dimensions: | Width: 28.3 cm<br>Height: 11.6 cm |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Material: | Metal, 0.8 mm |
| Dimensions: | Width: 46.5 cm<br>Height: 28.5 cm |
| Thread: | M4 thread x 8 mm |

**ROADINGER Flightcase 4x LED CLS-18 QCL RGB/WW with wheels**

| | |
|---|---|
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes |
| Material: | Plywood multi-layer glued, 9 mm |
| Color: | Black, laminated |
| Device compartment: | 12 cm x 40 cm x 28 cm |
| Accessory compartment: | 11 cm x 46.5 cm x 28 cm |
| Dimensions: | Width: 87.5 cm<br>Depth: 52.5 cm<br>Height: 44 cm |
| Weight: | 19.10 kg |

## Scope of delivery:

1 x device
1 x power cord
1 x frost filter
1 x remote control
1 x battery
4 x knurled screw
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.