EUROLITE LED PST-15W MK2 COB RGBW Floor Spot/Wash

Pinspot with 15 W COB LED, beam angles 4°/6°/20° (frost filter)

Art. No.: 51916251

GTIN: 4026397566451











Features:

- Additional frost filter provides a wide, soft and homogeneous light
- 1 LED 15 W high-power 4in1 RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable
- Strobe effect
- 4 integrated show programs
- Can be operated in 4; 6; 7 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; RDM; master/slave function
- Flicker-free
- With a beam angle of 4°
- With double bracket
- OLED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended; on stand

Logistic

EAN / GTIN: 4026397566451
Weight: 1,57 kg
Length: 0.29 m
Width: 0.19 m
Heigth: 0.14 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	17 W

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I
Power connection:	Mains input via IEC (M) power supply cord with safety plug (provided)
Power output:	1 x IEC (F)
Lamp type:	LED lamp
LED type:	1 x 15 W high-power 4in1 RGBW (homogenous color mix)
DMX channels:	4; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; RDM; master/slave function
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	4°
Beam angle (1/2 peak):	4° 6° 20°
Beam angle (1/10 peak):	7° 11° 35°
Housing color:	Black
Attachment system:	Double bracket
Display type:	OLED display
Material:	Aluminum casting
Dimensions:	Width: 13.5 cm Depth: 19 cm Height: 22 cm
Weight:	1.42 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm; 2 x Ø3mm
Material:	Aluminum, 3 mm
Cable construction:	3 x 1.0 mm² H05VV-F
Cable length:	Approx. 1.3 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Dimensions:	Width: 0.2 cm Diameter: Ø 8.2 cm
Material:	Metal, 2 mm
Color:	Black

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
2 x frost filter
1 x lamp clamping ring
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.