EUROLITE LED IP PT-100/34 RGB/WW Pixel DMX Tube

Weather-proof DMX pixel tube with RGB/WW color mixing

Art. No.: 51928619

GTIN: 4026397733112











Features:

- 102 LEDs 0.5 W SMD 5050 4in1 RGB/WW (homogenous color mix)
34 segments controlled separately
- Color change adjustable; Dimmer electronic; program speed adjustable; color animations with two adjustable colors
- 12 integrated show programs
- Direct color selection for 19 preset colors
- Can be operated in 3; 4; 6; 9; 13; 20; 68; 136 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function
- Flicker-free
- With a beam angle of 120°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; video and photography; advertisement/Shop window
- Silent operation
- Application possibility: Suspended; wall mounting

Logistic

EAN / GTIN: 4026397733112
Weight: 4,39 kg
Length: 1.04 m
Width: 0.10 m
Heigth: 0.21 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power consumption:	40 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Fuse:	5 x 20 mm, F 1 A fuse serviceable
Lamp type:	LED lamp
LED type:	102 x 0.5 W SMD 5050 4in1 RGB/WW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 6; 9; 13; 20; 68; 136
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function
Fixtures available for:	Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Housing color:	Black
Attachment system:	Ø 10mm 2x mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 100.1 cm Width: 7.0 cm Height: 16.8 cm
Weight:	3.84 kg
Noise classification:	Class 0 (no noise at all)

Scope of delivery:

1 x light effect
1 x power cord
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.