OMNITRONIC VFM-212AP MK2 2-way Speaker active TWS

Art. No.: 11038054

GTIN: 4026397732207

Active 2-way speaker system (12") with 140 W RMS for PA and DJ applications with audio player and Bluetooth











Features:

- 2-way bass-reflex enclosure with 30 cm woofer and 2.5 cm compression driver
- Class A/B circuitry: optimum sound and power at low weight and compact dimensions
- Stereo Bluetooth link for wireless stereo operation with 2 systems linked together
- SD card slot and USB port
- 2 mic/line inputs (XLR/6.3 mm jack) with separate level controls
- Line input, RCA
- Mixed output for linking further active speaker systems
- Master control with 2-band EQ
- Control via Bluetooth; IR remote control
- Black metal grille
- 3 Rugged carrying handles
- For application areas such as: Mobile djs / entertainer
- Application possibility: Standing; monitoring; on stand

Logistic

EAN / GTIN: 4026397732207
Weight: 13,70 kg
Length: 0.65 m
Width: 0.40 m
Heigth: 0.40 m

Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	420 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 2 A fuse replaceable

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power:	Program: 280W Rated: 140W RMS
Frequency range:	45 - 20000 Hz
Max. SPL:	120 dB
Control:	Bluetooth; IR remote control
Bluetooth:	Version: 5 with stereo link (TWS)
Bluetooth device name:	OMNITRONIC
Audio player:	USB + SD + Bluetooth
Attachment system:	Flange: Ø 35mm
Control elements:	Level control per channel, Master control, power switch, tone control, audio player
Status LED:	Power, clip
Connections:	Input: mic/line via 2 x 3-pin XLR Input: mic/line via 2 x 6.3 mm plug (unbal.) Input: line via 1 x stereo RCA Output: line via stereo RCA
Input channels:	2 x mono via XLR or jack, channel control via rotary dial 1 x stereo with line-player switch via RCA or player, channel control via rotary dial
Equalizer:	Master: 1 x 2-band tone control
Music format:	MP3, WAV
Number of files:	Max. 999
Available storage media:	USB devices/SD cards (FAT 32)
Speaker:	1 x woofer 12" with ferrit magnet Basket material: steel Conematerial: cardboard/paper Voice coil lows 1,5" 1 x compression tweeter highs 1" with ferrit magnet Voice coil compression tweeter highs 1" Horn vent 1"
Type of speaker:	Compact cabinet speaker
Carrying handle:	3 pc/pcs
Material:	Plastic
Color:	Black
Dimensions:	Width: 35.2 cm Depth: 34.8 cm Height: 59 cm
Weight:	12.20 kg
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x compact cabinet speaker
1 x remote control
1 x battery
1 x power cord
1 x user manual
1 x declaration of conformity

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.