# EUROLITE Set LED B-40 HCL Beam Effect MK2 wh + Case

**Art. No.: 20000960**

GTIN: 4026397718393










## Features:

**EUROLITE LED B-40 HCL Beam Effect MK2 wh**

LED beam effect with RGBWA+UV color mixing, incl. remote-control

- 5 LEDs 10 W  6in1 RGBWA/UV<BR> segments controlled separately
- Color blend stepless; Dimmer electronic; Rotation speed stepless
- Multi beam effect; strobe effect
- 8 integrated show programs
- Can be operated in 3; 12; 23 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended

**ROADINGER Flightcase 1x B-40 HCL/Laser**

Trunk case, HIGHLINE version

- High-quality workmanship with birch multiplex 6.5 mm, dark brown

## Logistic

EAN / GTIN: 4026397718393
Weight: 15,00 kg
Length: 0.00 m
Width: 0.00 m
Heigth: 0.00 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 2 high-quality spring locks
- Branded hardware
- European engineering

## Technical specifications:

| | |
|---|---|
| Weight: | 10.72 kg |

**EUROLITE LED B-40 HCL Beam Effect MK2 wh**

| | |
|---|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 56 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | IEC connector (F) mounting version |
| Fuse: | T 1.6 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 5 x 10 W 6in1 RGBWA/UV |
| Flash rate: | 0.6 - 12 Hz |
| DMX channels: | 3; 12; 23 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function |
| Fixtures available for: | Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Housing color: | White |
| Attachment system: | Omega bracket |
| Display type: | Monochrome 4 digit 7-segment LED display |
| Dimensions: | Length: 32.00 cm<br>Width: 32.00 cm<br>Height: 39.00 cm |
| Weight: | 4.22 kg |
| Noise classification: | Class 2 (slight noise) |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

**ROADINGER Flightcase 1x B-40 HCL/Laser**

| | |
|---|---|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 20 mm |
| Case handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Spring lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 6.5 mm, laminated |
| Color: | Dark brown |
| Device compartment: | 32.5 cm x 32.5 cm x 39 cm |
| Dimensions: | Length: 40 cm<br>Width: 40 cm<br>Height: 48 cm |
| Weight: | 6.50 kg |

## Scope of delivery:

1 x light effect
1 x user manual
1 x power cord
1 x omega bracket
4 x screw
4 x washer
1 x remote control
1 x battery

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.