OMNILUX®

# OMNILUX HX600 GKV LL240V/600W G-9.5 750h

**Art. No.: 88323003**

GTIN: 4026397266887




## Features:

- Dimmable
- Very high color rendering index (CRI)

## Technical specifications:

| | |
|---|---|
| Operating voltage: | 240 V |
| Nominal wattage: | 600 W |
| Base: | G-9.5 |
| Lamp type: | Incandescent lamp; halogen lamp |
| Lamp specification: | Dimmable |
| Beam angle: | 310° |
| Color of light: | White |
| Color temperature: | 3000K |
| Color rendering index (CRI): | 99.6 Ra |
| Lead time: | 0.2 s |
| Construction: | Bi pin |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |

## Logistic

EAN / GTIN: 4026397266887
Weight: 0,03 kg
Length: 0.11 m
Width: 0.04 m
Heigth: 0.04 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

| | |
|---|---|
| Burning position: | S180 (universal) |
| Lamp life: | 750 h |
| Luminous flux: | 12000 lm |
| Wavelength: | 778 nm |
| Dimensions (LxD): | 100x18 mm |
| Weight: | 0.02 kg |
| Energy efficiency class (A - G): | G |
| EPREL-Nr: | 1193592 |

## Scope of delivery:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.