EUROLITE RETRO BOWL 1

Warm white retro spotlight with colored LED rings

Art. No.: 51916650

GTIN: 4026397761962











Description:

This spotlight is a real eye-catcher. Its rustic housing combines classic design with modern technology. At the center of the reflector is a high-output 200 W LED that emits warm white light. When dimmed, it is ideal for mood lighting; at full brightness, it can serve as a powerful blinder.

The reflector itself is illuminated by 48 LEDs, whose color mixing is based on red, green, and blue, enabling hundreds of different colors. Additionally, the ring around the edge of the reflector is equipped with LEDs in RGB color mixing.

The spotlight features a double bracket that allows for use in a standing position. It can also be used suspended or mounted on a tripod.

Three different DMX modes are available for DMX control. In the smallest mode, the two rings and the central LED can be controlled. The larger modes additionally offer various effects and macros. The DMX signal can be fed via three-pin or five-pin cables. Additionally, a USB port for wireless DMX is available, which can be equipped with a QuickDMX or CRMX receiver.

Features:

- Mains input and output for power linking up to 8 units
  spotlight
- Dimmer electronic; color blend stepless; color fade stepless; color change adjustable; color selection manual; program selection; program speed adjustable; mood lights
- Wash effect; strobe effect; twinkle effect
- 15 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 7; 13; 15 CH mode

Logistic

EAN / GTIN: 4026397761962
Weight: 5,35 kg
Length: 0.38 m
Width: 0.39 m
Heigth: 0.29 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- The device is cooled by temperature-controlled fan at the head
- Control via CRMX by LumenRadio via USB (optional); stand-alone; sound to light; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Flicker-free
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; stage; mobile djs / entertainer; restaurants, bars and hotels; rental; video and photography
- Application possibility: Standing; suspended; on stand

power cord

- Built with SEETRONIC connector

mounting bracket

- With double bracket

Technical specifications:

Display type:	Monochrome 4 digit 7-segment LED display
Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	180 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version Bypass
Fuse:	T 8 A fuse serviceable
Lamp type:	LED lamp
Flash rate:	1 - 20 Hz
DMX channels:	7; 13; 15
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	1 x temperature-controlled fan at the head
Control:	CRMX by LumenRadio via USB (optional); stand-alone; sound to light; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
PWM frequency:	22000 Hz
DMX fail mode:	Blackout
Beam angle (1/2 peak):	Spot 40°
Beam angle (1/10 peak):	Spot 89°
Color temperature:	2900K
Lamp life:	10000 h
Housing color:	Black matte
USB port:	Type A
Material:	Metal, painted
Material thickness:	2 mm
Dimensions:	Length: 40 cm Depth: 23 cm Height: 36 cm Diameter: Ø 32 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	4.70 kg
Noise classification:	Class 2 (slight noise)
Cable length:	1.2 m
Use of brands:	Built with SEETRONIC connector
Attachment system:	Double bracket
Diameter mounting holes:	4 x Ø8.2mm

Scope of delivery:

1 x spotlight
1 x user manual
1 x power cord
2 x mounting bracket
4 x screw
4 x washer

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.