RELACART PM-320R In-Ear Bodypack Receiver 626-668 MHz

In-ear stereo wireless receiver with diversity technology

Art. No.: 13055246

GTIN: 4026397712407











Description:

The PM-320 is a wireless in-ear monitoring system delivering outstanding sound for live performances, theater and voice applications. Diversity technology guarantees optimum reception quality without interference or dropouts. The system can be operated in mono and stereo mode. The bodypack receiver is 100 g light and offers perfect wearing comfort.

Features:

- Stereo pocket receiver with 317 preset channels and 5 user-defined channels for in-ear monitoring
- Sturdy all-metal housing with soft-touch controls, applicable for touring
- Diversity technology for high reception quality
- Pilot frequency squelch technology delete wireless RF interference
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Stereo or mono/mix mode
- Balance (left, right) adjustable
- Limiter and high frequency boost
- Lock function for prevents undesired changes to settings
- Powered by a battery/battery pack
- Operating range up to 100m with line-of-sight
- Up to 5 transmitters can be operated in parallel without interference
- OLED display
- Charge status indicator

Logistic

EAN / GTIN: 4026397712407
Weight: 0,27 kg
Length: 0.29 m
Width: 0.12 m
Heigth: 0.07 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Type:	In-ear monitor
Battery:	2 x Mignon (AA) (not included)
Frequency range:	25 - 15000 Hz
S/N ratio:	>100 dB
THD:	<0.9 % at 1 kHz
Range:	Up to 100m with line-of-sight
Frequency band:	UHF 628 - 668 MHz
Diversity:	Antenna diversity
Switching bandwidth:	42 MHz
Frequency stability:	± 0.005 %
Parallel mode:	Max. 5 transmitter
Modulation:	FM, stereo
Frequency selection:	202 switchable frequencies In 20 groups
Display type:	OLED display
Display reading:	Charge status indicator , frequency , goup , channel; AF audio level , RF signal level
Status LED:	Antenna A/B
Connections:	Output: headphones via 1 x 3.5 mm jack (stereo) mounting version
Material:	Aluminum
Dimensions:	Width: 6.5 cm Depth: 2.3 cm Height: 9 cm
Weight:	0.11 kg

Scope of delivery:

1 x receiver
1 x user manual
1 x declaration of conformity

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.