EUROLITE LED B-40 HCL Beam Effect MK2 wh

LED beam effect with RGBWA+UV color mixing, incl. remote-control

Art. No.: 51918953

GTIN: 4026397713190











Features:

- 5 LEDs 10 W 6in1 RGBWA/UV
 segments controlled separately
- Color blend stepless; Dimmer electronic; Rotation speed stepless
- Multi beam effect; strobe effect
- 8 integrated show programs
- Can be operated in 3; 12; 23 CH mode
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
- With omega bracket
- Monochrome 4 digit 7-segment LED display
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; advertisement/Shop window
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397713190

Weight: 6,05 kg

Length: 0.41 m

Width: 0.40 m

Heigth: 0.52 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	56 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power output:	IEC connector (F) mounting version
Fuse:	T 1.6 A fuse replaceable
Lamp type:	LED lamp
LED type:	5 x 10 W 6in1 RGBWA/UV
Flash rate:	0.6 - 12 Hz
DMX channels:	3; 12; 23
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); master/slave function
Fixtures available for:	Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	White
Attachment system:	Omega bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Length: 32.00 cm Width: 32.00 cm Height: 39.00 cm
Weight:	4.22 kg
Noise classification:	Class 2 (slight noise)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x light effect
1 x user manual
1 x power cord
1 x omega bracket
4 x screw
4 x washer
1 x remote control
1 x battery

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.