PSSO PXS ONE 1-channel True Diversity Receiver 640-665 MHz

Art. No.: 13063507

GTIN: 4026397752328

License-free true diversity wireless receiver with auto scan, 3-band EQ, TFT color display & rack kit





Features:

- Professional multifrequency wireless receiver with true diversity reception for stage use
- High-grade components and intelligent features ensure best performance and high reliability
- Ideal for large multi-channel systems
- Up to 54 transmitters in 4 bands can be operated in parallel without interference
- Automatic frequency setup
- Spectrum analysis to identify interference frequencies
- Operating range up to 200m
- Multifunctional jogdial for menu settings
- 2 detachable BNC antennas allow for use with external antenna divider
- Multicolor TFT display
- Charge status indicator
- (19") 48.3 cm rack installation possible 1 U

Logistic

EAN / GTIN: 4026397752328
Weight: 2,25 kg
Length: 0.42 m
Width: 0.32 m
Heigth: 0.07 m

Technical specifications:

Type:	Receiver
Power supply:	100-240 V AC, 50/60 Hz 12V DC 1000 mA
Power consumption:	3.6 W
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) power supply cord with AC adapter (provided)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Number of channels:	1
Frequency range:	30 - 19000 Hz
S/N ratio:	>112 dB
THD:	<0.5 % at 1 kHz
Range:	Up to 200m
Frequency band:	UHF 640 - 665 MHz
Diversity:	True diversity
Switching bandwidth:	25 MHz
Frequency stability:	± 0.001 %
Parallel mode:	Max. 54 transmitter in 4 bands
Frequency selection:	Frequencies automatically scannable
Housing color:	Black
Display type:	Multicolor TFT display
Display reading:	Frequency , goup , channel , charge status indicator; RF signal level , AF audio level , antenna A/B , Mute
Control elements:	Power switch, encoder, exit, sync button
Status LED:	Power
Connections:	Input: antenna via 2 x BNC (F) 11.54 V Output: microphone via 1 x 6.3 mm plug (unbal.) Output: microphone via 1 x 3-pin XLR (M) mounting version
Equalizer:	3-band tone control
USB port:	2 x type C
Material:	Metal
Mounting dimensions:	23 cm x
Housing design:	(19") 48.3 cm rack installation possible 1 U
Dimensions:	Width: 21.2 cm Depth: 24.4 cm Height: 4.5 cm
Weight:	1.80 kg
Dimensions:	Length: 100 cm

Scope of delivery:

1 x receiver
2 x antenna
1 x external mains adapter
1 x transmitter
1 x USB cable
1 x jack cable
1 x mounting bracket
6 x screw
1 x battery pack

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.