

LAVOCE DN20.300T 2" Compression Driver, Neodymium Magnet

Art. No.: 12602839

GTIN:







Features:

- Available in various sizes

Logistic

Technical specifications:

Power:	Program: 220W Rated: 110W AES
Frequency range:	500 - 20000 Hz
Sensitivity:	108.5 dB
Impedance:	8 ohms
Connections:	2 x solder tail
Speaker:	Compression tweeter highs 2" with neodymium magnet Diaphragmmaterial: titanium Voice coil compression tweeter highs 3"
Color:	Black
Weight:	2.23 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Scope of delivery:

1 x speaker

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.